



- Single phase and DC input
- Short circuit, overload, input and output overvoltage protections
- Over temperature protection
- Suitable for standard applications
- Isolation Class 2, no grounding needed



NOTE

Please refer to the datasheet for more details
Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance



CODE	XCS1015W024VAA	XCS1015W012VAA
TYPE	CSD1-015W/024V/AA	CSD1-015W/012V/AA
INPUT TECHNICAL DATA		
Input rated voltage	120–230 Vac	120–230 Vac
Input voltage AC	85...264 Vac	85...264 Vac
Input voltage DC	100...370 Vdc (derating U _{in} <130 Vdc)	100...370 Vdc (derating U _{in} <130 Vdc)
Frequency	47...63 Hz	47...63 Hz
Current consumption	0.29 A (120 Vac) / 0.18 A (230 Vac)	0.29 A (120 Vac) / 0.18 A (230 Vac)
Inrush peak current	5 A	5 A
Power factor	> 0.6	> 0.6
Internal protection fuse	T 1 A	T 1 A
External protection on AC line	MCB: C-2 A / Fuse: T-2 A	MCB: C-2 A / Fuse: T-2 A
OUTPUT TECHNICAL DATA		
Output rated voltage	24 Vdc ±1%	12 Vdc ±1%
Output adjustable range	—	—
Continuous current	0.6 A at 60°C	1.2 A at 60°C
Overload limiting	0.81 A	1.6 A
Short circuit peak current	—	—
Ripple @ nominal ratings	50 mVpp	50 mVpp
Hold up time	12 ms (120 Vac) / 20 ms (230 Vac)	12 ms (120 Vac) / 20 ms (230 Vac)
Status indication	LED "DC OK"	LED "DC OK"
Alarm contact	—	—
Parallel connection	possible	possible
Redundant parallel connection	possible with external ORing diode	possible with external ORing diode
GENERAL TECHNICAL DATA		
Efficiency	86% (120 Vac) / 86% (230 Vac)	84% (120 Vac) / 85% (230 Vac)
Dissipated power	2.2 W (120 Vac) / 2.2 W (230 Vac)	2.7 W (120 Vac) / 2.6 W (230 Vac)
Operating temperature range	-20...+70°C (derating -0.9 W >60°C)	-20...+70°C (derating -0.9 W >60°C)
Input / output isolation	3 kVac / 60 s (SELV output)	3 kVac / 60 s (SELV output)
Input / ground isolation	class 2 without PE connection	class 2 without PE connection
Output / ground isolation	class 2 without PE connection	class 2 without PE connection
Standard / approvals	EN 60950-1, EN 62368-1	EN 60950-1, EN 62368-1
EMC Standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Overvoltage category / Pollution degree	II / 2	II / 2
Protection degree	IP 20	IP 20
Connection terminal IN/OUT	2.5 mm ² / 2.5 mm ²	2.5 mm ² / 2.5 mm ²
Housing material	UL94V-0 plastic material	UL94V-0 plastic material
Dimension	35x62x90 mm	35x62x90 mm
Approximate weight	91 g	91 g
Mounting information	vertical on a rail, 10 mm from adjacent components	vertical on a rail, 10 mm from adjacent components
APPROVALS		
ACCESSORIES		
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
Marking tag	—	—