

POWER SUPPLIES - QUICK SELECTION TABLE



POWER

OUTPUT RATED VOLTAGE [VDC]	OUTPUT ADJUSTABLE RANGE [VDC]	CONTINUOUS CURRENT [A]	OUTPUT POWER [W]	INPUT RATED VOLTAGE [VAC]	PHASE NO.	INPUT VOLTAGE RANGE [VAC]	INPUT VOLTAGE RANGE [VDC]	ALARM CONTACT	REDUNDANT VERSION	TYPE	CODE	PAGE
1.2...24	—	0.3...1.5	30	12-24	1	10...26	-	—	—	CL1R	XCL1R	58
1.2...24	—	0.8...5	120	12-24	1	10...26	-	—	—	CL5R	XCL5R	58
12...15	12...15	7	85	—	—	—	18...36	—	—	CSA120CB	XCSA120CB	55
12	—	1.2	15	120-230	1	85...264	100...370	—	—	CSD1-015W/012V/AA	XCSD1015W012VAA	13
12	—	4...2.0	30	120-230	1	85...264	100...370	—	—	CSD1-030W/012V/AA	XCSD1030W012VAA	14
12	12...15	5...4	72	120-230	1	85...264	100...370	—	—	CSD1-072W/012V/AA	XCSD1072W012VAA	16
12	12...15	6	85	120-230	1	90...264	100...345	•	—	CSF85B	XCSF85B	20
12	12...15	8 - 7	96	230-400-500	1-2	187...550	270...725	•	—	CSW121B	XCSW121B	44
12	12...15	16 - 17	192	230-400-500	1-2-3	185...550	270...770	•	—	CSW241B	XCSW241B	45
12-24	11.5 ... 29	100	2400	400-500	3	340...550	—	•	•	CSG2401C	XCSG2401C	53
24	—	0.6	15	120-230	1	85...264	100...370	—	—	CSD1-015W/024V/AA	XCSD1015W024VAA	13
24	—	1.2	30	120-230	1	90...264	100...320	—	—	CSF30C	XCSF30C	18
24	—	1.25	30	120-230	1	85...264	100...370	—	—	CSD1-030W/024V/AA	XCSD1030W024VAA	14
24	23.5... 27.5	3	72	120-230	1	85...264	100...370	—	—	CSD1-072W/024V/AA	XCSD1072W024VAA	16
24	16 ... 28	3	72	120-230	1	85...264	100...370	•	—	CSL1-072W/024V/AA	XCSL1072W024VAA	27
24	23...27.5	3.5	85	120-230	1	90...264	100...345	•	—	CSF85C	XCSF85C	19
24	23...27.5	3.5	85	120-230	1	90...264	100...345	•	•	CSF85CP	XCSF85CP	19
24	23...27.5	5	120	120-230	1	90...264	100...345	•	—	CSF120C	XCSF120C	21
24	23...27.5	5	120	120-230	1	90...264	100...345	•	•	CSF120CP	XCSF120CP	21
24	16 ... 28	5	120	120-230	1	85...264	100...370	•	—	CSL1-120W/024V/AA	XCSL1120W024VAA	27
24	24...27.5	5	120	230-400-501	1-2	187...550	270...725	•	—	CSW121C	XCSW121C	44
24	22.5...27.5	5	120	—	—	—	10.5...18	—	—	CSA120BC	XCSA120BC	55
24	22.5...27.5	5	120	—	—	—	18...36	—	—	CSA120CC	XCSA120CC	56
24	22.5...27.5	5	120	—	—	—	36...72	—	—	CSA120DC	XCSA120DC	56
24	23...27.5	10	240	120-230	1	90...132 / 185...264	300...345	•	—	CSF240C	XCSF240C	23
24	23...27.5	10	240	120-230	1	90...132 / 185...264	300...345	•	•	CSF240CP	XCSF240CP	23
24	23...27.5	10	240	120-230	1	90...132 / 185...264	—	—	—	CSL240C	XCSL240C	29
24	24...27.5	10	240	230-400-500	1-2-3	185...550	270...770	•	—	CSW241C	XCSW241C	45
24	23...27	10	240	—	—	—	100...130	—	•	CSA240FC	XCSA240FC	57
24	24 ... 28	20	480	120-230	1	90...132 / 185...264	259...370	•	•	CSF500C	XCSF500C	25
24	20 ... 28	20	480	120-230	1	85...264	100...370	•	—	CSL1-480W/024V/AA	XCSL1480W024VAA	30
24	20 ... 28	20	480	120-230	1	85...264	100...370	•	—	CSL1-480W/024V/GA	XCSL1480W024VGA	30
24	20 ... 28	20	480	120-230	1	85...264	100...370	•	—	CSL1-480W/024V/AB	XCSL1480W024VAB	31
24	23.3...27.5	20	480	230-400-500	1-2-3	187...550	250...725	•	—	CSW481C	XCSW481C	47
24	24...28	20	480	400-500	2-3	340...550	—	•	—	CSG500C	XCSG500C	50
24	20 ... 28	20	480	400-500	3	340...550	—	•	—	CSL3-480W/024V/AA	XCSL3480W024VAA	36
24	20 ... 28	20	480	400-500	3	340...550	—	•	—	CSL3-480W/024V/GA	XCSL3480W024VGA	36
24	20 ... 28	20	480	400-500	3	340...550	—	•	—	CSL3-480W/024V/AB	XCSL3480W024VAB	37
24	24...28	30	720	400-500	2-3	340...550	—	•	—	CSG720C	XCSG720C	51
24	23...27.5	40	960	230 / 400-500	1-2	180...264 / 360...550	550...775	•	•	CSW960CP	XCSW960CP	48
24	24...28	40	960	400-500	2-3	340...550	—	•	—	CSG960C	XCSG960C	51
24-48	23 ... 56	50	2400	400-500	3	340...550	—	•	•	CSG2401D	XCSG2401D	53

- INFORMATION AVAILABLE
- INFORMATION NOT AVAILABLE

POWER SUPPLIES - QUICK SELECTION TABLE



OUTPUT RATED VOLTAGE [VDC]	OUTPUT ADJUSTABLE RANGE [VDC]	CONTINUOUS CURRENT [A]	OUTPUT POWER [W]	INPUT RATED VOLTAGE [VAC]	PHASE NO.	INPUT VOLTAGE RANGE [VAC]	INPUT VOLTAGE RANGE [VDC]	ALARM CONTACT	REDUNDANT VERSION	TYPE	CODE	PAGE
48	45...55	2.5	120	120-230	1	90...264	100...345	•	•	CSF120DP	XCSF120DP	22
48	45...55	5	240	120-230	1	90...132 / 185...264	300...345	•	•	CSF240DP	XCSF240DP	24
48	45...55	10	480	120-230	1	90...132 / 185...264	259...370	•	•	CSF500D	XCSF500D	25
48	40.5 ... 55.5	10	480	120-230	1	85...264	100...370	•	—	CSL1-480W/048V/AA	XCSL1480W048VAA	32
48	40.5 ... 55.5	10	480	120-230	1	85...264	100...370	•	—	CSL1-480W/048V/GA	XCSL1480W048VGA	32
48	40.5 ... 55.5	10	480	120-230	1	85...264	100...370	•	—	CSL1-480W/048V/AB	XCSL1480W048VAB	33
48	45...55	10	480	230-400-500	1-2-3	187...550	250...725	•	—	CSW481D	XCSW481D	47
48	40.5 ... 55.5	10	480	400-500	3	340...550	—	•	—	CSL3-480W/048V/GA	XCSL3480W048VGA	38
48	40.5 ... 55.5	10	480	400-500	3	340...550	—	•	—	CSL3-480W/048V/AB	XCSL3480W048VAB	39
48	40.5 ... 55.5	10	480	400-500	3	340...550	—	•	—	CSL3-480W/048V/AA	XCSL3480W048VAA	38
48	45...55	20	960	400-500	2-3	340...550	—	•	•	CSG960D	XCSG960D	52
72	72...85	6	430	230-400-500	1-2-3	187...550	250...725	•	—	CSW481G	XCSW481G	48
72	62.5 ... 81	6.6	480	120-230	1	85...264	100...370	•	—	CSL1-480W/072V/AA	XCSL1480W072VAA	34
72	62.5 ... 81	6.6	480	120-230	1	85...264	100...370	•	—	CSL1-480W/072V/GA	XCSL1480W072VGA	34
72	62.5 ... 81	6.6	480	120-230	1	85...264	100...370	•	—	CSL1-480W/072V/AB	XCSL1480W072VAB	35
72	60 ... 81	6.6	480	400-500	3	340...550	—	•	—	CSL3-480W/072V/GA	XCSL3480W072VGA	40
72	60 ... 81	6.6	480	400-500	3	340...550	—	•	—	CSL3-480W/072V/AB	XCSL3480W072VAB	41
72	60 ... 81	6.6	480	400-500	3	340...550	—	•	—	CSL3-480W/072V/AA	XCSL3480W072VAA	40
72	72...85	13.3	960	400-500	2-3	340...550	—	•	•	CSG960G	XCSG960G	52
72	50 ... 87	33	2400	400-500	3	340...550	—	•	•	CSG2401G	XCSG2401G	54
100-110-170	88...175	14	2400	400-500	3	340...550	—	•	•	CSG2401R	XCSG2401R	54

- INFORMATION AVAILABLE
- INFORMATION NOT AVAILABLE